



FEATURES

- Consistent reliability with high accuracy
- Low cost
- Thermocouple / RTD / DCV / DC mA
- Compact size

APPLICATION

PLC Panels
 Automation
 Feeder / motor
 Generator
 Transformer
 Electrical Dist.

SPECIFICATION

Aux. Supply	: 230 / 110 VAC 50/60Hz (-20%+15%)
Burden on Aux.	: < 3 VA
Range	: PT 100 -70 C to 500 C J 0 - 750 C K 0 - 1200 C R 0 - 1750 C S 0 - 1750 C
Signal Input	: 0 - 10 VDC, 0 - 20mA
Resolution	: Temperature Input : 1°C Signal Input : 0.001, 0.01, 0.1 & 1
Temp	: -20°C to +55°C
Humidity	: < 95% RH (non condensing)
Dimension	: 96 x 96 x 48 mm (L x W x D) 96 x 48 x 58 mm (L x W x D)
Weight	: 300 gms

Counter

**MODEL
VIPS 901**

FEATURES

- Consistent reliability with high accuracy
- Low cost
- 6 Digit Totaliser
- Input Speed upto 1 KHz
- Compact size

SPECIFICATION

Aux. Supply	: 90 - 270 V AC 50/60 Hz /DC
Burden on Aux.	: < 3 VA
Input Speed	: 0 - 1 KHz
Range	: 999999
Direction	: Up counting
Input	: Sensor NPN / PNP / Potential Free Contact
Sensor Supply	: 12VDC , 30 mA in built
Relay Contacts	: Potential Free Contact (NO&NC)
Contact Rating	: 6 Amps / 230 V AC/ 28 V DC
Temp	: -20°C to +55°C
Humidity	: < 95% RH (non condensing)
Dimension	: 36 x 72 x 73 mm (L x W x D)
Weight	: 250 gms



APPLICATION

PLC Panels
 Automation
 Feeder / motor
 Generator
 Transformer
 Electrical Dist.

Other Products Manufactured



Panel Meter



Engine PU



CT



Transducer



Temperature



UV/OV/PR



Timer


 Earth Leakage
 Relay & CBCT