



FEATURES

- Consistent reliability with high accuracy
- Low cost
- Time Delay user settable (4 Ranges)
- LED indication for Power & Relay status
- Compact size
- ON Delay / OFF Delay modes of operations

APPLICATION

Control Panel
Feeder / motor
Generator
Transformer
Electrical Dist.

SPECIFICATION

Aux. Supply	: 230VAC 50/60 Hz & 24V AC/DC	Reset Time: <100mSec. on power interruption
	: 110VAC 50/60Hz & 24V AC/DC	Temp : -20°C to +55°C
Time Ranges	: 15 / 60 Sec. 7.5 / 60 min.	Humidity : < 95% RH (non condensing)
Relay Contacts	: 1 Potential Free Contact (NO & NC)	Dimension : 17.5 x 91 x 64 mm (WxLxH)
Contact Rating	: 5 Amps / 230 V AC/ 28 V DC	Mounting : Din (35 mm rail) / 2 x m4 screw
Accuracy	: +/- 5% of full Scale	Weight : 150 gms
Repeatability	: +/- 0.5%	

FORWARD REVERSE Timer

MODEL
VIPS 99 FPR

FEATURES

- Consistent reliability with high accuracy
- Low cost
- ON Time & Pause Time user settable
- LED indication for Forward & Reverse Relay
- Compact size

APPLICATION

Control Panel
Feeder / motor
Generator
Transformer
Electrical Dist.

SPECIFICATION

Aux. Supply	: 230VAC 50/60 Hz & 24V AC/DC	Reset Time: <100mSec. on power interruption
	: 110VAC 50/60Hz & 24V AC/DC	Temp : -20°C to +55°C
ON Time Ranges	: 1 / 2 / 4 / 8 min.	Humidity : < 95% RH (non condensing)
Pause Time Ranges	: 10 / 20 / 40 / 80 sec.	Dimension : 22.5 x 77 x 105 mm (WxLxH)
Relay Contacts	: 1 Potential Free Contact (NO & NC)	Mounting : Din (35 mm rail) / 2 x m4 screw
Contact Rating	: 5 Amps / 230 V AC/ 28 V DC	Weight : 120 gms
Accuracy	: +/- 5% of full Scale	
Repeatability	: +/- 0.5%	



Other Products Manufactured



Panel Meter



Engine PU



CT



Transducer



Temperature



UV/OV/PR



Timer



Earth Leakage
Relay & CBCT