



FEATURES

- Programmable : A) Under/Over Voltage
B) Under/Over Frequency
C) Phase Fail
D) Phase Reversal
E) Voltage Asymmetry
- Configurable for 3Phase & 1 Phase system
- Individual Faults can be deactivated as per system requirement
- Programmable Delay & Hysterises
- Auto / Manual Reset option
- Consistent reliability with high accuracy
- 3 Digit Bright Display to indicate voltage & Frequency
- LED indication for healthy / faulty status

APPLICATION

- Protection :
- Control Panel
 - Feeder / motor
 - Generator
 - Transformer
 - Electrical Dist.

SPECIFICATION

System	: 3 Phase 4 wire / 1 Phase system	Temp	: -20°C to +55°C
Burden on Supply	: < 3 VA	Humidity	: < 95% RH (non condensing)
Delay	: 0.2 Sec. to 99 Sec.	Dimension	: 90 x 45 x 75 mm (L x B x H)
Relay Contacts	: 1 Potential Free Contact (NO,C & NC)(De-Energise on Trip)	Mounting	: Din (35 mm rail) / 2 x m4 screw
Contact Rating	: 8 Amps / 230 V AC/ 28 V DC	Weight	: 200 gms
Nominal Voltage	: 240VAC		
Set Point	: Voltage : +/- 25% of nominal Hz : +/- 10 Hz Voltage Asymmetry : 0 - 99 V Hysterisis : 1% - 10%		

Other Products Manufactured



Panel Meter



Engine PU



CT



Transducer



Temperature



UV/OV/PR



Timer



Earth Leakage
Relay & CBCT