



**Features:**

- ▶ Consistent Reliability with high accuracy
- ▶ Trip setting through front panel potentiometer
- ▶ Time delay user settable
- ▶ LED Indication for healthy/faulty status
- ▶ Compact size
- ▶ Under voltage/Over voltage/phase reversal



**Advantages:**

- ▶ Protection of power assets
- ▶ Detection and isolation of faults
- ▶ Speedy tripping to avoid damage
- ▶ Maintain supply continuity of healthy circuit

**Applications:**

- ▶ Switchgear distribution system
- ▶ Feeder/Motor protection
- ▶ Energy management
- ▶ Equipment and network protection
- ▶ Over load protection
- ▶ Control Panel protection
- ▶ Generator Protection
- ▶ Transformer protection
- ▶ Electrical Distribution protection

**Input Specification**

System	1Ø-2 wire/3Ø-4 wire
Burden on Supply	< 3 VA
Delay	0.2 to 30 sec

**Mechanical Specification**

Dimension	78x17.5x97 mm (LxBxH)
Mounting	DIN Rail (35mm)
Weight	75 g

**Set Point**

Set Point	±25% of nominal voltage for UV,Ov
-----------	-----------------------------------


**Output Specifications**

Relay Contacts	1 Potential free Contact (NO, C & NC)
De-energise	On fault
Contact Rating	6A/230V AC/28V DC
Nominal Voltage	380/415/440V AC


**Environmental Specifications**

Operating Temperature	-10 deg C to 55 deg C
Storage Temperature	-20 deg C to 75 deg C
Humidity	<95 RH

**Dimension**



**Connection Diagram**



**Ordering Information**

Ordering Code	Description
VIPS101	UV/OV/PR Voltage Relay